

Smoothie & Slush Machines



ASM Smoothie & Slush Machines



SLUSH MACHINE - 12LITER CAPACITY

- Unbreakable & non-poisonous P.C 12liter(3.17gallon) capacity bowl.
 (Maximum mix capacity is 9liter.)
- Stainless steel body and case for long life.
- O Durable metal geared motor for long life and reliability.
- TC & Torque control system.











SSM-180

Tank capacity: 12Liter(3.17gallon) X 1

Weight: 30Kg (66.2 lbs)

SLUSH MACHINE - 7.5LITER CAPACITY

- O Perfect performance in tropical zone.
- O Fastest freezing ability.
- O Unbreakable & non-poisonous P.C 7.5liter (1.98gallon) capacity bowl.
- O TC & Torque control system. [Drain cap] [Drip guidance] [Air filter] [Drain box] adapted.







SSM-52

· Tank capacity: 7.5Liter(1.98gallon) X 2

· Weight: 38Kg (83.8 lbs)





SSM-420



SSM-280

· Tank capacity: 12Liter(3.17gallon) X 2

· Weight: 52Kg (114.7 lbs)

· Tank capacity: 12Liter(3.17gallon) X 3 · Weight: 80Kg (176.4 lbs)

SSM-560

· Tank capacity: 12Liter(3.17gallon) X 4 · Weight: 160Kg (352.8 lbs)

Multi-Purpose **ALL IN ONE**

Slush & Soft Ice Cream Machines are combined.

You can enjoy Slush & Yogurt together.









SSM-280 · Tank capacity: 12Liter(3.17gallon) X 2 · Weight: 52Kg (114.7 lbs)

SSI-151TG · Cylinder capacity: 1.4Liter(0.37gallon) X 1 · Weight: 90Kg (198 lbs)



ALL IN ONE





ISM-72L

CLAS	SIFICATION	SPECIFICATION	
	MODEL	ISM-72L (FROZEN BEVERAGE)	
PROD	DUCT NAME	SLUSH MACHINE	
BODY	SIZE(WXDXH) / mm SIZE(WXDXH) / Inch	410 X 430 X 730 (Including Cover) 16.1x16.9x28.7 (Including Cover)	
	Power Consumption	500W	
Electrical Features	Running Current	3.6A	
Electrical reatures	Geared Motor	2 EA	
	Fan Motor	10 W	
	Compressor	Fully Closed	
	Condenser	Pin tube type	
Freezing	Evaporator	Drum Type	
	Cooling Type	Capillary Tube	
	Refrigerant	R-134A	
	Proper Material Quantity	3,0L X 2TANK (Maximum 5L)	
Miscellaneous	Control Method	LCD BUTTON, MICOM CONTROL	
Miscellalleons	Operation Environment	Ambient Temperature: 10~38°C Voltage Rating: 115V/60Hz, 208~230V/60Hz, 220~240V/5	



SSM-180

Dimensions (W x D x H)	195×487×837(mm) 7 7×19 2×33 0(inch)		
Weight	30Kg (66.2lbs)		
Legs	Rubber Packing		
Power consumption	320W		
Geared Motor	67W×1EA		
Refrigerant	R-134a		
Compressor	0.35HP		
Voltage Rating	115V/60Hz, 208~230V/60Hz, 220~240V/50HZ		
Optional accessories	_		



SSM-280

Dimensions	395×468×897(mm)
(W x D x H)	15.6×18.5×35.4(inch)
Weight	51Kg(112.5lbs)
Legs	Rubber Packing
Power consumption	1,020VV
Geared Motor	67W×2EA
Refrigerant	R-404a
Compressor	0.85HP
Voltage Rating	115V/60Hz, 208~230V/60Hz,
voltage natifig	220~240V/50HZ
Optional accessories	Supporting Table



SSM-420

598×468×897(mm) 23.6×18.5×35.4(inch)
75Kg(165.4lbs)
Rubber Packing
1,350VV
67W×3EA
R-404a
0.85HP (50Hz spec), 1.30HP (60Hz spec)
115V/60Hz, 208~230V/60Hz, 220~240V/50HZ
Supporting Table



SSM-560

Dimensions (W x D x H)	795×502×1,307(mm) 31.3×19.8×51.5(inch)
Weight	160Kg(352.8lbs)
Legs	Casters
Power consumption	2,040VV
Geared Motor	67W×4EA
Refrigerant	R-404a
Compressor	0.85HP×2EA
Voltage Rating	208~230V/60Hz, 220~240V/50HZ
Ontional accessories	_



SSM-52

Dimensions (W x D x H)	420×380×705(mm) 16.6×7.1×27.8(inch)		
Weight	38Kg (83.8lbs)		
Legs	Adjustable leveler		
Power consumption	500W		
Geared Motor	67×2EA		
Refrigerant	R134a		
Compressor	0.5HP		
Voltage Rating	115V/60Hz, 208~230V/60Hz, 220~240V/50HZ		

^{*} The product's design and specification is subject to change without prior notice.



ALL IN ONE

825×724×1.500(mm) 32.5×28.5×59.1(inch)		
190Kg(419lbs)		
Slush Part : Same as SSM-280		
oft Ice Cream Part		
10liter (2.64gallon)		
1.4liter (0.37gallon)		
0.37KW		
12Kg/h(26.5lbs/h)		
6~8min		
5~6cups(100cc/3.5oz)		
0.85HP(R404a)		
0.35HP(R134a)		
208~230V/60Hz, 220~240V/50HZ		

^{*} Product's exterior and specification can be modified without prior notice.

Manufactured by:



Any queries call 0447587446 PLEASE NOTE NEW PHONE NUMBER 044 SLUSHGO Full information can be found at : www. AustralianSlushMachines.com.au

Distributed i	by:			